WHAT IS CLAIMED IS:

1. A method of repairing a light emitting device comprising a step of applying a first voltage and a second voltage to a light emitting element in order, wherein the first voltage and the second voltage are reverse bias voltages of different levels.

2. A method according to claim 1, wherein the first voltage and the second voltage are within ± 15% of an avalanche voltage of the light emitting element.

3. A method according to claim 1, wherein the light emitting element is an electroluminescence element.

4. A method according to claim 1, wherein the light emitting device is included in an electric device selected from the group consisting of a video camera, a digital camera, a goggle type display, a head mounted display, a navigation system, an audio reproducing device, a car audio, an audio component, a notebook computer, a game machine. a portable information terminal, a mobile computer, a cellular phone, a portable game machine, an electronic book, an image reproducing device, and a digital versatile disk (DVD) player.

5. A method of repairing a light emitting device comprising a step of gradually changing a voltage applied to a light emitting element from a first voltage to a second voltage, wherein the first voltage and the second voltage are reverse bias voltages of different levels.

6. A method according to claim 5, wherein the first voltage and the second voltage are within ± 15% of an avalanche voltage of the light emitting element.

7. A method according to claim 5, wherein the light emitting element is an electroluminescence element.

8. A method according to claim 5, wherein the light emitting device is included in an electric device selected from the group consisting of a video camera, a digital camera, a goggle type display, a head mounted display, a navigation system, an audio reproducing device, a car audio, an audio component, a notebook computer, a game machine, a portable information terminal, a mobile computer, a cellular phone, a portable game machine, an electronic book, an image reproducing device, and a digital versatile disk (DVD) player.

9. A method of repairing a light emitting device comprising a step of:

applying a first voltage and a second voltage in order between an anode and a cathode of the light emitting device,

wherein the anode and the cathode are located in a light emitting element with a light emitting layer interposed therebetween, and

wherein the first voltage and the second voltage are reverse bias voltages of different levels.

10. A method according to claim 9, wherein the first voltage and the second voltage are within ± 15% of an avalanche voltage of the light emitting element.

11. A method according to claim 9, wherein the light emitting element is an electroluminescence element.

12. A method according to claim 9, wherein the light emitting device is included in an electric device selected from the group consisting of a video camera, a digital camera, a goggle type display, a head mounted display, a navigation system, an audio reproducing device, a car audio, an audio component, a notebook computer, a game machine, a portable information terminal, a mobile computer, a cellular phone, a portable game machine, an electronic book, an image reproducing device, and a digital versatile disk (DVD) player.

13. A method of repairing a light emitting device comprising a step of:

gradually changing a voltage applied between an anode and an cathode of the light emitting device from a first voltage to a second voltage,

wherein the anode and the cathode are located in a light emitting element with a light emitting layer interposed therebetween, and

wherein the first voltage and the second voltage are reverse bias voltages of different levels.

14. A method according to claim 13, wherein the first voltage and the second voltage are within ± 15% of an avalanche voltage of the light emitting element.

15. A method according to claim 13, wherein the light emitting element is an electroluminescence element.